

Undo Glue Hook & Gel - Selleys

Canonical: <https://www.selleys.com.au/products/glues-adhesives/removable-hooks-and-glue/undo-glue-hook-gel/>

Details:

Undo Glue Hook & Gel - Selleys DIY Trade FIND A STORE Search for products and articles Products Projects FAQ By Range Adhesives Sealants Putty & Fillers Tiling Cleaning Painting Car Care Accessories Flooring Brands Liquid Nails Undo Glue No More Gaps Selleys 600 Series Wet Area Silicone Most Popular Products No More Gaps Multipurpose Liquid Nails Original Wet Area Silicone Sealant Rapid Mould Killer Original Sugar Soap By Projects Repair Woodworking Paint Preparation Caulking Upcycling Projects Craft Projects By Room Kitchen Bathroom Living Areas Outdoor Beginner Tips Glue Guide 101 How to Use a Caulking Gun Types of Gap Fillers Products Products Application Brands Sealants Adhesives Fillers Building Carpentry Plumbing Glazing Tiling Flooring Roofing Painting Waterproofing Plastering Liquid Nails No More Gaps Selleys 600 Series Wet Area Silicone Aquadhere Storm Sealant DIY Trade By Range Adhesives Sealants Putty & Fillers Tiling Cleaning Painting Car Care Accessories Flooring Brands Liquid Nails Undo Glue No More Gaps Selleys 600 Series Wet Area Silicone Most Popular Products No More Gaps Multipurpose Liquid Nails Original Wet Area Silicone Sealant Rapid Mould Killer Original Sugar Soap Brands Liquid Nails Undo Glue No More Gaps Selleys 600 Series Wet Area Silicone By Range Adhesives Sealants Putty & Fillers Tiling Cleaning Painting Car Care Accessories Flooring Most Popular Products No More Gaps Multipurpose Liquid Nails Original Wet Area Silicone Sealant Rapid Mould Killer Original Sugar Soap Most Popular Products No More Gaps Multipurpose Liquid Nails Original Wet Area Silicone Sealant Rapid Mould Killer Original Sugar Soap By Range Adhesives Sealants Putty & Fillers Tiling Cleaning Painting Car Care Accessories Flooring Brands Liquid Nails Undo Glue No More Gaps Selleys 600 Series Wet Area Silicone Products By Range Brands Most Popular Products By Projects Repair Woodworking Paint Preparation Caulking Upcycling Projects Craft Projects By Room Kitchen Bathroom Living Areas Outdoor Beginner Tips Glue Guide 101 How to Use a Caulking Gun Types of Gap Fillers By Room Kitchen Bathroom Living Areas Outdoor By Projects Repair Woodworking Paint Preparation Caulking Upcycling Projects Craft Projects Beginner Tips Glue Guide 101 How to Use a Caulking Gun Types of Gap Fillers Beginner Tips Glue Guide 101 How to Use a Caulking Gun Types of Gap Fillers By Projects Repair Woodworking Paint Preparation Caulking Upcycling Projects Craft Projects By Room Kitchen Bathroom Living Areas Outdoor Projects By Projects By Room Beginner Tips DIY Products Projects FAQ Products Sealants Adhesives Fillers Application Building Carpentry Plumbing Glazing Tiling Flooring Roofing Painting Waterproofing Plastering Brands Liquid Nails No More Gaps Selleys 600 Series Wet Area Silicone Aquadhere Storm Sealant Trade Products Application Brands Home Product Glues & Adhesives Removable Hooks & Glue Undo Glue Hook & Gel < > Features Strong hold (hook & glue) Easy removal - twist to undo No damage* Holds up to 2kg, 3kg and 5kg (small, medium, large hook) Works on tiles, wood, metal, glass, ceramic, concrete, laminated timber, powder coated metal, most plastics* and painted walls Important Information • Ready to hang in 24 hours • Surfaces must be clean and dry • Twist to remove - do not pull • Wait a minimum of 28 days after painting • Not for polypropylene (PP) or polyethylene (PE) plastics Size 2pk Large 10pk Medium 4pk Medium 3pk Medium 10pk Small 4pk Small 3pk Small Buy Online Find a Store Share Share this Product with your friends Downloads Safety Data Sheet Technical Data Sheet Technical Details Limitations Directions For Use Technical Details Technology Hybrid Polymer Cure Mechanism Moisture curing Specific Gravity 1.03 Colour Clear Skin Time 30-60 minutes Curing Rate Approx. 4mm/24hrs Shore A Hardness 34 Application Temperature +5°C to +40 °C Service Temperature -20 °C to +70 °C Storage Temperature +5 °C to +25 °C Limitations Do not apply if the ambient or substrate surface temperature is below +5 °C or above +40 °C. Optimal application temperature is between +5 °C and +25 °C. At low temperatures, curing speed slows. Not suitable for extremely aged or compromised walls. The product

may leave a stain on porous surfaces. Wait a minimum of 28 days after painting to apply. Mechanically fix valuable items. For optimal performance, remove and re-apply glue every 2 years. Selleys® recommends users conduct their own risk assessment before use to determine the product's suitability. A sample should be applied to the intended area to ensure acceptable appearance, finish, and performance on the substrate.

Directions For Use HOOKS Apply the adhesive along the marked application lines on the back of the hook. Use an amount of adhesive appropriate to the size of the hook. Position the hook against the intended surface and apply firm, even pressure for approximately 30 seconds to ensure adequate contact. Allow the adhesive to cure fully before applying any load. Refer to the Load Capacity table for the relevant hook size

LIGHTWEIGHT MOUNTABLE MATERIALS Apply the adhesive in dots approximately 10-15 mm in diameter, positioned about 30 mm from the edge of the material - 2 dots for approximately A4-size or smaller - 4 dots for approximately A3-size - 6 dots for approximately A2-size Position the material on the desired surface and apply firm, even pressure for approximately 30 seconds to ensure good contact. Allow the adhesive to fully cure before use. Undo Grip or hold the edges of the hook or the attached item and firmly twist it anticlockwise to remove. Never pull towards you, as this may damage the wall or surface. Peel any residue from both the surface and the hook/item, then clean as necessary. Notes: As a guide, to facilitate clean removal, allow the adhesive to fully cure prior to removal. Under typical conditions, the product may remain adhered to porous substrates for up to 3 days and to non-porous substrates for up to 5 days before removal. For any remaining adhesive on textured surfaces, we recommend using Selleys Sealant Remover for easy clean-up.

Surface Ensure all bonding surfaces are clean, structurally sound, and free from dust, oil, rust, or any other contaminants. The product is suitable for use on both dry and damp surfaces. For non-porous substrates, clean the surface using a clean cloth lightly moistened with IPA or white spirit. Wipe in a single direction only, then immediately follow with a clean, dry cloth to remove any remaining residue.

Tube Remove the cap and use the reverse end of the cap to carefully pierce the seal on the tube. Squeeze the tube from the base to dispense the product. Once the desired amount has been dispensed, replace the cap securely. Retain the packaging for future reference and use.

Storage Store unopened packaging below 25 °C in a cool, dry place away from direct sunlight. Long-term exposure to elevated temperature can decrease material mechanical performance. Unopened packaging is best used within 12 months from the date of manufacture.

FAQs What is Undo Glue? Undo Glue is a removable adhesive designed for use with hooks or by itself for lightweight hanging and mounting. It provides strong hold while allowing clean removal when used according to instructions. Will Undo Glue damage my wall? Undo Glue is designed for damage-free removal when used on a suitable surface and removed according to instructions. Twist the hook to undo. Do not pull it directly away from the wall. How long before I can hang something? Allow 24 hours for Undo Glue to reach full strength before loading the hook. How much weight can it hold? The small, medium and large hooks hold up to 2kg, 3kg and 5kg respectively, when applied and used as directed. Can I reuse Undo Glue? The adhesive is single use. The hook can be reused with fresh Undo Glue. Can I use it without a hook? Yes. Undo Glue can be applied directly to lightweight posters, prints, paper and decorations. Peel to undo. What surfaces should I avoid? Do not use on PP or PE plastics, extremely aged or compromised walls, or freshly painted surfaces. Wait at least 28 days after painting. The product may stain porous surfaces.

PRODUCT SELECTOR PROJECT GUIDES CONTACT US SAFETY DATA SHEETS About Selleys Selleys Stories Contact us Glossary terms Selleys and Sustainability Products Adhesives Sealants Painting Fillers Putty Home Cleaning Car Care Brands Liquid Nails No More Gaps Wet Area Storm Power Grip Aquadhere BBQ Tough DIY Tasks Bathroom projects Kitchen projects Living room projects Outdoor projects Woodwork Projects Upcycle Projects Craft Projects More Find your nearest store Safety Data Sheets Competition Terms & Conditions About Selleys Selleys Stories Contact us Glossary terms Selleys and Sustainability Products Adhesives Sealants Painting Fillers Putty Home Cleaning Car Care Brands Liquid Nails No More Gaps Wet Area Storm Power Grip Aquadhere BBQ Tough DIY Tasks Bathroom projects Kitchen projects Living room projects Outdoor projects Woodwork Projects Upcycle Projects Craft Projects More Find your nearest store Safety Data Sheets Competition Terms & Conditions About Us Contact Us Selleys New Zealand © 2026 All Rights Reserved Selleys Australia & New Zealand Privacy Policy Site terms Site Map Menu ×

